

INSTALLATION OF 1.5 CAM ARM ASSEMBLY

58524

1. Remove tank from Omen
2. Degas marker
3. Remove all Paintballs from marker
4. Turn to page 12 in Omen Owners Manual 1.1
5. Using a 5/32 Allen key remove part # 7 (Pivot Cover Screw/ Sear Plate Screw)
6. Rotate part # 4 (Pivot Cover) up and out of the way
7. Using a 1/16 Allen key remove part # 3 (Cover Plate Screw)
8. Remove part # 2 (Cover Plate)
9. Using a small flat head screw driver remove part # 6 (Cam Pin Threaded)
Note: Once unscrewed you will have to push the Cam Pin out from the bottom using a .050 Allen Key.
10. Remove part # 84 (Cam Arm Assembly)
11. Install new part # 84 (Cam Arm Assembly)
12. Using a small flat head screw driver reinstall part #6 (Cam Pin Threaded)
13. Reinstall part #2 (Cover Plate)
14. Using a 1/16 Allen Key reinstall part # 3 (Cover Plate Screw)
15. Rotate part # 4 (Pivot Cover) back down
16. Using a 5/32 Allen Key reinstall # 7 (Pivot Cover Screw/Sear Plate Screw)
17. Kill Fools.....

